

SPECIFICATION DATA



Electrochemical Toxic Gas Detector GT3000 Series Includes Transmitter (GTX) and Sensor Module (GTS)



DESCRIPTION

The Det-Tronics GT3000 line of electrochemical gas detectors is designed to provide continuous monitoring of the atmosphere for potentially hazardous gas leaks or oxygen depletion. Models are available for detecting a variety of gas types in various concentration ranges.

The GT3000 toxic gas detector is a two-wire loop powered device and is designed as a stand alone unit that supports local calibration. It is also fully compatible with the FlexVu® UD10/UD20/UD30 Universal Display Units.

The GT3000 consists of a replaceable sensor module (GTS) connected to a transmitter module (GTX). The transmitter generates a 4-20 mA output signal with HART, which is proportional to the concentration of the target gas and directly corresponds to 0-100% full scale.

The electrochemical sensor cell uses capillary diffusion barrier technology for monitoring gas concentrations in ambient air. When compared to solid state type sensors, the electrochemical sensing element provides improved accuracy, stability and reliability, and can also extend calibration intervals. This results in superior performance and reliability, as well as reduced maintenance.

HIGHLIGHTS

- ▲ Performance approved and verified
- ▲ Electrochemical sensor cell for increased accuracy, stability and reliability
- ▲ Highly specific response reduces the chance of false alarms resulting from the presence of other gases
- ▲ Self-contained transmitter circuitry
- ▲ Temperature compensated to ensure consistent performance over entire operating temperature range
- ▲ Suitable for outdoor applications requiring IP66 rating
- ▲ Hydrophobic filter easily replaced without opening the device or use of tools
- ▲ Hot swappable IS sensor module for live maintenance without de-classification of hazardous area
- ▲ EMI/RFI hardened
- ▲ Event and calibration logs are stored in non-volatile memory and are accessible using a UD10/UD20/UD30, HART device or AMS software.
- ▲ Real-time clock with battery back-up
- ▲ Magnetic switch and LEDs for user interface



SPECIFICATIONS

Calibration	Sensors are calibrated at the factory. Gas type and range are read by the transmitter. Calibration is initiated at the detector, at the UD10/UD20 Universal Display Unit, or by some other HART interface device. Calibration cannot be initiated from the UD30.			Certification		
Operating Voltage	24 Vdc nominal; Operating range is 12 to 30 Vdc			Explosion-Proof Model	FM:	Class I, Div. 1, Groups A, B, C & D Class I, Zone 1, Group IIC IP66 Conduit seal not required Acidic atmospheres excluded
Power Consumption	0.8 watt maximum @ 30 Vdc				CSA:	Class I, Div. 1, Groups A, B, C & D (T6) Class I, Div. 2, Groups A, B, C & D (T6) IP66
Max. Loop Resistance	300 ohms at 18 Vdc, 600 ohms at 24 Vdc				IECEX:	Ex d mb [ia Ga] IIC T4 Gb IP66 IECEX FMG 10.0003X
Current Output	4-20 mA (Normal operating mode) 3.8 mA indicates calibrate mode 3.5 mA or less indicates a fault condition				INMETRO:	UL-BR 15.0752X Ex db mb [ia Ga] IIC T4 Gb IP66 Tamb -40°C to +50°C (H ₂ S) Tamb -20°C to +50°C (other)
Wiring	2x22 AWG, 1x16 AWG, 600V, 20"			Intrinsically Safe Model	FM:	IS Class I, Div. 1, Groups A, B, C & D Class I, Zone 0, Group IIC Performance verified per ANSI/ISA 92.00.01 and FM6340 IP66
Storage Temp. (GTX)	-55°C to +75°C (-67°F to +167°F)				CSA:	Class I, Div. 1, Groups A, B, C & D (T4) IP66
(GTS)	0°C to +20°C (+32°F to +68°F) Ideal: +4°C to +10°C (+39°F to +50°F)				IECEX:	Ex ia IIC T4 Ga IP66 IECEX FMG 08.0005X
Storage Life	6 months in factory-sealed packaging				INMETRO:	UL-BR 15.0404X Ex ia IIC T4 Gb IP66 Tamb -40°C to +50°C
Humidity Range	15 to 90% RH.			SIL Approval	IEC 61508 Certified SIL 2 Capable SIL Certification includes H ₂ S, H ₂ S+ and O ₂ models only	
Tropicalization / PC BD Protection	Conformal coated printed circuit boards: CTI Rating of 600V, maximum allowed by standard Third party tested per ASTM-D-3638-07					
Pressure Range	Atmospheric ±10%					
Warm-Up	Warm-up time can last up to 150 seconds					
Thread Options	3/4" NPT or M25					
Enclosure Material	GTX Transmitter: 316 Stainless Steel GTS Sensor Module: PPA (30% Carbon filled)					
Expected Operating Life	GTS: 2 years in an open air environment					
Expected Shelf Life	GTS: 6 months in factory sealed packaging					
Warranty (For the GTX. See Table below for the GTS)	18 months from date of shipment					

FM Approvals Performance Approved Electrochemical Gas Sensors

Gas	Range	Response Time ¹	Operating Temperature Range	Accuracy / Repeatability (Whichever is greater)	Performance Approved Standard	Zero Drift	Storage Temperature Range	Warranty (from ship date)
Hydrogen Sulfide+ (H ₂ S+)	0-20 PPM	T20 = ≤10 Sec., T50 = ≤13 Sec., T90 = ≤30 Sec.	For -10°C to +55°C, ±2 ppm or ±10% of Reading ⁶ , ISA 92.00.01 ⁴ . For -20°C to -10°C, ±3 ppm or ±15% of Reading ⁶ , Det-Tronics Verified. For -40°C to -20°C, ±3 ppm or ±30% of Reading ⁶ , Det-Tronics Verified.			± 1 ppm/Mo.	10°C to 30°C	18 months
Hydrogen Sulfide+ (H ₂ S+)	0-50 PPM					± 1 ppm/Mo.	10°C to 30°C	18 months
Hydrogen Sulfide+ (H ₂ S+)	0-100 PPM					± 2 ppm/Mo.	10°C to 30°C	18 months
Ammonia (NH ₃)	0-100 PPM ²	T50 = 24 Sec., T90 = 65 Sec.	For +20°C to +40°C, ±4ppm or ±15% of Reading ⁶ , Det-Tronics Verified. For -10°C to +20°C, ±4ppm or -20% to +50% of Reading ⁶ , Det-Tronics Verified. For -20°C to -10°C, ±4ppm or -20% to +60% of Reading ⁶ , Det-Tronics Verified.			± 2 ppm/Mo.	0°C to 20°C	12 months
Ammonia (NH ₃)	0-500 PPM ²	T50 = 30 Sec., T90 = 120 Sec.	For +20°C to +40°C, ±4ppm or ±15% of Reading ⁶ , Det-Tronics Verified. For -20°C to +20°C, ±4ppm or -15% to +40% of Reading ⁶ , Det-Tronics Verified.			± 10 ppm/Mo.	0°C to 20°C	12 months
Oxygen (O ₂) ⁵	0-25% V/V ³	T20 = 7 Sec., T90 = 30 Sec.	-20°C to +50°C	< 0.5% V/V ⁷	FM6340 ⁴	< 2 %/Mo.	0°C to 20°C	18 months
Carbon Monoxide (CO)	0-100 PPM	T50 = 15 Sec., T90 = 40 Sec.	For +20°C to +50°C, ±5ppm or ±10% of Reading ⁶ , Det-Tronics Verified. For -20°C to +20°C, ±6ppm or ±25% of Reading ⁶ , Det-Tronics Verified.			± 2 ppm/Mo.	0°C to 20°C	18 months
Carbon Monoxide (CO)	0-500 PPM	T50 = 12 Sec., T90 = 25 Sec.				± 9 ppm/Mo.	0°C to 20°C	18 months
Sulfur Dioxide+ (SO ₂ +)	0-20 PPM	T50 = 12 Sec., T90 = 30 Sec.	For -40°C to +55°C, ±0.6ppm or ±15% of Reading ⁶ , Det-Tronics Verified.			± 0.4 ppm/Mo.	0°C to 20°C	12 months
Sulfur Dioxide+ (SO ₂ +)	0-100 PPM	T50 = 15 Sec., T90 = 35 Sec.	For -40°C to +55°C, ±0.6ppm or ±15% of Reading ⁶ , Det-Tronics Verified.			± 0.4 ppm/Mo.	0°C to 20°C	12 months
Chlorine (Cl ₂)	0-10 PPM	T50 = ≤14 Sec., T90 = ≤34 Sec.	For +20°C to +50°C, ±0.6ppm or ±30% of Reading ⁶ , Det-Tronics Verified. For -20°C to +20°C, ±0.6ppm or -40% to +60% of Reading ⁶ , Det-Tronics Verified.			< 0.2 ppm/Mo.	0°C to 20°C	12 months
Hydrogen (H ₂)	0-1000 PPM	T50 = 8 Sec., T90 = 60 Sec.	For +20°C to +40°C, ±50ppm or ±10% of Reading ⁶ , Det-Tronics Verified. Operating range is down to -20°C.			± 20 ppm/Mo.	0°C to 20°C	18 months
Nitrogen Dioxide (NO ₂)	0-20 PPM	T50 = 7 Sec., T90 = 31 Sec.	For +20°C to +40°C, ±2ppm or ±10% of Reading ⁶ , Det-Tronics Verified. Operating range is down to -20°C.			± 0.1 ppm/Mo.	0°C to 20°C	12 months

¹ Time to reach percentage of final reading when gas concentration equal to full scale is applied to sensor (per ISA 92.00.01).

² Background concentrations of Ammonia may shorten lifetime of sensor.

³ Sensor approved for Oxygen depletion (< 21% V/V) only.

⁴ Performance Approved by FM Approvals.

⁵ Oxygen sensor will indicate fault if <1% volume oxygen is detected.

⁶ Accuracies only apply to initial gas exposure and temperature-range testing at 50% of full scale (ISA 92.00.01).

⁷ Accuracies only apply to temperature-range testing at 20.9 percent Oxygen (per FM 6340).



Corporate Office
6901 West 110th Street
Minneapolis, MN 55438 USA
www.det-tronics.com

Phone: +1 952.941.5665
Toll-free: +1 800.765.3473
Fax: 952.829.8750
det-tronics@carrier.com



© 2023 Carrier.